

# Veedol ATF VI

Material no. 03204P257

## DESCRIPTION

**Veedol ATF VI** is a very high grade automatic transmission fluid based on selected synthetic base oils with a high viscosity index together with a number of advanced additives. This red coloured ATF gives the following benefits:

- Longer life time of the fluid
- Very strong dispersion restricting sludge to a minimum
- High resistance to oxidation and thermal stress
- High resistance to wear, corrosion and foam
- Targeted friction properties
- Perfect compatibility with seals and non-ferro metals
- Exceeds the properties of Dexron III and II fluids

## APPLICATION

This fluid may be used for automatic gear boxes, power steering units, torque converters and other equipment, for which an ATF exceeding Dexron III and Dexron II is required. This product cannot be used in DCTs and CVTs or when an oil with the Ford Type F/G specification is recommended.

## PERFORMANCE SPECIFICATIONS

GM Dexron VI  
MB 236.41  
Voith H55.6335xx

## TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.850
Kinematic viscosity at 40°C, ASTM D445, mm <sup>2</sup> /s	31
Kinematic viscosity at 100°C, ASTM D445, mm <sup>2</sup> /s	6.2
Viscosity index, ASTM D2270	154
Pour point, ASTM D6892, °C	- 45
Brookfield viscosity at -40°C, ASTM D2983, mPa.s	<=20000
Colour, VISUAL	RED