

Veedol ATF M-15

Material no. 03204T258

DESCRIPTION

Veedol ATF M-15 is a high grade full synthetic automatic transmission fluid formulated with a number of special base oils and additives. It gives the following benefits:

- Reduced viscosity for maximum fuel efficiency
- Adapted friction coefficient behaviour for comfortable shifting processes
- Reliably prevents bothersome friction vibrations and stick-slip effects
- Outstanding friction coefficient consistency over the entire shifting interval
- Excellent low-temperature shifting behaviour
- Highest oxidation and ageing stability

APPLICATION

Veedol ATF M-15 is adapted to the special requirements of Mercedes-Benz 7-speed automatic transmissions (NAG 2 FE+). Its optimised friction coefficient system ensures comfortable shifting processes even under full load and performance is maintained over the entire change interval.

PERFORMANCE SPECIFICATIONS

Veedol recommends for

Infiniti Matic-G
MB 236.15
Nissan Matic-G

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.847
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	20,9
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	4,79
Viscosity index, ASTM D2270	158
Pour point, ASTM D6892, °C	-48
Brookfield viscosity at -40°C, ASTM D2983, mPa.s	3500
Flash Point COC, ASTM D9, °C	178
Colour, VISUAL	DARK BLUE