

Veedol Turbostar S 20W-50

Material no. 03202M028

DESCRIPTION

Veedol Turbostar S 20W-50 is a multigrade engine oil, suitable for older diesel engines in all working conditions and during the whole year. It gives the following benefits:

- Excellent properties against wear, corrosion and foaming
- Extended oil drain intervals

APPLICATION

This engine lubricant is suitable for older diesel engines (normal or turbo-aspirated), even with wide variations. It is also suitable for most gasoline engines in light use.

PERFORMANCE SPECIFICATIONS

ACEA A3/B3, A3/B4, E3
API CG-4/SJ, CF-4/SG

Veedol recommends for

MIL L-2104 E/L-46152 E
Allison C4
Caterpillar TO-2
Cummins CES 20071/72
Daimler Truck DTFR 15B110
Mack EO-L
MAN 271/M3275-1
MB 227.1/228.1/228.3/229.1
MTU Oil Category 1/2
Volvo VDS-2

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.891
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	150
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	17.7
Viscosity index, ASTM D2270	130
B.N. (HClO ₄ method), ASTM D2896, mg KOH/g	8.5
Pour point, ASTM D6892, °C	-33
CCS viscosity at -15°C, ASTM D5293, mPa.s	8200
Sulfated Ash, ASTM D874, Mass %	1.18
Flash Point COC, ASTM D92, °C	235