

# Veedol Gear Oil LD 75W-80

Material no. 03203P203

## DESCRIPTION

**Veedol Gear Oil LD 75W-80** is a full synthetic lubricating oil for mechanical transmissions, formulated with high quality synthetic base oils and special EP additives to give the following benefits:

- Good clutch-switch performance at low temperatures
- Excellent thermal stability
- Very high activity against wear, corrosion and foam
- Low pour point
- Very high quality EP properties
- Long drain interval
- Fuel economy

## APPLICATION

This gear oil is specially developed for gearboxes under very heavy duty conditions, together with high temperatures. This oil can also be used for extended drain intervals.

## PERFORMANCE SPECIFICATIONS

API GL-4

### Veedol recommends for

DAF  
Daimler Truck DTFR 13B150  
Eaton Extended drain  
Iveco  
MAN 341 E-3/Z-4  
MB 235.4  
Renault B0032/2 Annex 3  
Volvo 97307/97305  
ZF TE-ML 01L/02L/08/13/16K/24A

## TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.856
Kinematic viscosity at 40°C ASTM D445, mm <sup>2</sup> /s	54.6
Kinematic viscosity at 100°C ASTM D445, mm <sup>2</sup> /s	9.43
Viscosity index ASTM D2270	157
Pour point, ASTM D6892, °C	-42
Brookfield viscosity at -40°C, ASTM D2983, mPa.s	80000
Flash Point COC, ASTM D92, °C	234