

Veedol Gear Oil RPC 75W80

Material no. 03203P204

DESCRIPTION

Veedol Gear Oil RPC 75W-80 is a universal, multigrade lubricating oil for mechanical transmissions, with EP properties. Due to the addition of high quality solvent refined base oils and special additives, this gear oil has the following benefits:

- Very high activity against wear, corrosion and foam
- Excellent resistance to oxidation
- Low viscosity at low temperatures
- Very good EP properties
- High and stable viscosity index

APPLICATION

This special transmission oil is used in gearboxes where a good clutch-switch performance is necessary. It is suitable for nearly all manual gearboxes of passenger cars. This gear oil can also be used where the manufacturer of the gearbox prescribes a gear oil with a low viscosity.

PERFORMANCE SPECIFICATIONS

API GL-4 +
Ford WSS-M2C200-D2
Ford ESD-M2C186-A

Veedol recommends for

BMW 83 22 0 140 516
BMW 83220309031
BMW MTF LT-2
Fiat 9.55550-MX3/-MZ1
GM 1940182/1940768
Honda MTF 94

Hyundai 02200-00130 TOD
Land Rover TYK500030
MB 235.10
Mitsubishi MZ312644
Nissan 999MP-MTF20P
Nissan MT-XZ
PSA B71 2330/9730 A2/9730 A8
Subaru K0321-F0090
Toyota JWS 227
Volvo 97308/97309/97310
VW G 052 171/G 052 527/G 052 726/G 055 538

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.871
Kinematic viscosity at 40°C ASTM D445, mm ² /s	45.8
Kinematic viscosity at 100°C ASTM D445, mm ² /s	9.1
Viscosity index ASTM D2270	185
Pour point, ASTM D6892, °C	-45
Brookfield viscosity at -40°C, ASTM D2983, mPa.s	142.000
Flash Point COC, ASTM D92, °C	205