

Veedol Multigrade Super 10W40

Material no. 03201M014

DESCRIPTION

Veedol Multigrade Super 10W-40 motor oil is based on a combination of high quality solvent refined mineral and synthetic base oils. By adding a well balanced choice of additives the following benefits are obtained:

- High and stable viscosity index
- Fast cold start
- Strong resistance to oxidation
- Good detergency and dispersion
- Safe lubrication film at high temperatures
- Strong protection against wear, corrosion and foaming

APPLICATION

Veedol Multigrade Super 10W-40 is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans. It fulfils Euro 4 norms.

PERFORMANCE SPECIFICATIONS

ACEA A3/B3, A3/B4
API SN/CF

Veedol recommends for

Fiat 9.55535-D2/-G2
MB 229.1
RENAULT RN 0700/ RN 0710
VW 501 01/505 00

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.865
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	91
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	13.8
Viscosity index, ASTM D2270	155
B.N. (HCLO4 method), ASTM D2896, mg KOH/g	10.1
Pour point, ASTM D6892, °C	-39
CCS viscosity at -25°C, ASTM D5293, mPa.s	6700
Sulfated Ash, ASTM D874, Mass %	1.0
Flash Point, COC ASTM D92, °C	220