

Veedol Turbostar 20W50

Material no. 03201M017

DESCRIPTION

Veedol Turbostar 20W-50 is a modern multifunctional motor oil, produced with high quality solvent refined base oils and modern additives to give the following benefits:

- Good anti-wear properties
- Excellent protection against oxidation
- Extensive protection against corrosion and foam formation
- Strong dispersing and detergent power
- High and stable viscosity index
- Low evaporation rate

APPLICATION

This versatile engine oil is ideal for gasoline and diesel engines with or without turbocharging, in cars and vans.

PERFORMANCE SPECIFICATIONS

ACEA A3/B3, A3/B4
API SL/CF

Veedol recommends for

MB 229.1
PSA B71 2295
VW 501 01/505 00

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.892
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	155
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	18.0
Viscosity index, ASTM D2270	125
B.N. (HClO ₄ method), ASTM D2896, mg KOH/g	10.1
Pour point, ASTM D6892, °C	-27
CCS viscosity at -15°C, ASTM D5293, mPa.s	8800
Sulfated Ash, ASTM D874, Mass %	1,03
Flash Point COC, ASTM D92, °C	235