



Veedol Powertron Ultra 5W40

Material no. 03201P010

DESCRIPTION

Veedol Powertron Ultra 5W-40 motor oil is developed according to the most recent technology and based on specially selected synthetic base oils with a high natural viscosity index. With the addition of a well-balanced choice of advanced additives the following benefits are obtained:

- High resistance to shearing
- Fast cold start
- Safe lubrication film at very high temperatures
- Reduced formation of combustion ashes
- Very good detergency and dispersion
- Very strong protection against wear, corrosion and foaming

APPLICATION

Veedol Powertron Ultra 5W-40 motor oil is specially recommended for passenger car unit injector diesel engines. Further this lubricant is very suitable for use in petrol and diesel engines, with or without turbo-charging. This product meets the requirements of several OEMs and thus has a wide application. It provides reliable protection of after-treatment devices and diesel particulate filters. It is a mid SAPS oil corresponding to Euro 4 and Euro 5 norms.

PERFORMANCE SPECIFICATIONS

ACEA C3
API SN/CF
Ford WSS-M2C917-A

Approval
MB 229.51
VW 505 00/505 01

Veedol recommends for
BMW Longlife-04
Fiat 9.55535-GH2/S2
GM dexos2™
MB 226.5/229.31
Porsche A40
Renault RN 0700/RN 0710

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.851
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	84,7
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	13,9
Viscosity index, ASTM D2270	170
B.N. (HClO ₄ method), ASTM D2896, mg KOH/g	7,5
Pour point, ASTM D6892, °C	-39
CCS viscosity at -30°C, ASTM D5293, mPa.s	5970
Sulfated Ash, ASTM D874, Mass %	0,8
Flash Point COC, ASTM D92, °C	235