

Veedol Powertron FE 5W30

Material no. 03201P030

DESCRIPTION

Veedol Powertron FE 5W-30 is a fuel economy universal motor oil, developed according to the most recent technology, based on specially selected synthetic base oils to which advanced additives are added to give the following benefits:

- Fuel saving in partial and full load operation mode
- High and stable viscosity index
- Excellent shear stability
- Excellent cold-start properties
- Excellent protection against oxidation
- Reliable lubricant film, even at high temperatures
- Excellent detergent and dispersion properties
- Extensive protection against corrosion and foam formation

APPLICATION

Veedol Powertron FE 5W-30 is a fuel-saving motor oil especially formulated for modern gasoline engines in passenger cars.

PERFORMANCE SPECIFICATIONS

API SN/RC/SN Plus
ILSAC GF-5
Ford WSS-M2C945-A/-M2C946-A/-M2C947-A

Approval
dexos1TM Gen 2 Veedol

recommends for
Chrysler MS 6395
Fiat 9.55535-CR1

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.847
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	60.3
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	10.7
Viscosity index, ASTM D2270	168
B.N. (HClO ₄ method), ASTM D2896, mg KOH/g	9.2
Pour point, ASTM D6892, °C	-36
CCS viscosity at -30°C, ASTM D5293, mPa.s	4500
Sulfated Ash, ASTM D874, Mass %	0.94
Flash Point COC, ASTM D92, °C	221