

Veedol Powertron Racing 5W50

Material no. 03201P031

DESCRIPTION

Veedol Powertron Racing 5W-50 is a synthetic engine oil based on carefully selected high quality synthetic base oils, all of which already have a natural, high viscosity index and advanced and well balanced additives in order to give the following benefits:

- Good resistance to shearing
- Very low tendency to evaporation
- High and very stable viscosity index
- High resistance to ageing
- Safe lubrication film at low and very high temperatures

APPLICATION

A synthetic engine oil, designed for cars in sporty driving conditions where the highest performance is required. This oil has proven its quality under rigorous conditions.

PERFORMANCE SPECIFICATIONS

ACEA A3/B4
API SN/CF

Veedol recommends for
BMW Longlife-01
MB 229.3
VW 501 01/505 00

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.852
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	118
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	18.0
Viscosity index, ASTM D2270	170
B.N. (HClO ₄ method), ASTM D2896, mg KOH/g	9.6
Pour point, ASTM D6892, °C	-30
CCS viscosity at -30°C, ASTM D5293, mPa.s	6200
Sulfated Ash, ASTM D874, Mass %	1.1
Flash Point COC, ASTM D92, °C	235