

# Veedol Sintron C4 5W30

Material no. 03201T004

## DESCRIPTION

**Veedol Sintron C4 5W-30** is a fuel economy, universal motor oil, developed according to the most recent technology. Based on specially selected synthetic base oils and advanced additives, this low SAPS motor oil gives several benefits:

- Lower fuel consumption
- Suitable for modern catalysts
- Low combustion ash buildup (low SAPS)
- Fast cold start
- Safe lubrication film at high temperatures
- Very good detergency and dispersion
- Very strong protection against wear, corrosion and foaming

## APPLICATION

**Veedol Sintron C4 5W-30** is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans. Due to its special composition this product can be used in vehicles for which the Renault specification RN0720 is required. Due to its low SAPS content this motor oil contributes to the extension of the lifetime of particulate filters for diesel engines.

**Warning:** These oils have the lowest SAPS limits and may be unsuitable for use in some engines.

## PERFORMANCE SPECIFICATIONS

ACEA C4

### Approval

Renault RN 0720

### Veedol recommends for

Fiat 9.55535-S4

MB 226.51/229.51

## TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.852
Kinematic viscosity at 40°C, ASTM D445, mm <sup>2</sup> /s	67.1
Kinematic viscosity at 100°C, ASTM D445, mm <sup>2</sup> /s	11.8
Viscosity index, ASTM D2270	173
B.N. (HClO <sub>4</sub> method), ASTM D2896, mg KOH/g	6.4
Pour point, ASTM D6892, °C	-39
CCS viscosity at -30°C, ASTM D5293, mPa.s	5800
Sulfated Ash, ASTM D874, Mass %	0.5
Flash Point COC, ASTM D92, °C	220