

Veedol Sintron C3 Plus 5W40

Material no. 03201T033

DESCRIPTION

Veedol Sintron C3 Plus 5W-40 enhances the performance of several W12, V10 and V8 engines of several manufacturers. Its top quality properties are proven by the VW 511 00 and Porsche C40 specifications, which broadens the lubricant's applicability to a range of Audi, Bentley and Lamborghini cars.

APPLICATION

- Fuel economy: low fuel consumption and CO₂ emissions
- Aftertreatment protection: full aftertreatment device protection
- Total engine protection: outstanding engine cleanliness and durability

PERFORMANCE SPECIFICATIONS

ACEA C3
API SN/CF

Veedol recommends for

BMW Longlife-04
GM dexos2™
MB 226.5
MB 229.51
MB 229.52
Porsche C40
Renault RN 0700/0710
VW 511 00

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.850
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	73.0
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	13.5
Viscosity index, ASTM D2270	191
B.N. (HClO ₄ method), ASTM D2896, mg KOH/g	7.8
Pour point, ASTM D6892, °C	-42
Sulfated Ash, ASTM D874, Mass %	0.79
Flash Point COC, ASTM D92, °C	222