

Veedol Sintron J 0W16

Material no. 03201T024

DESCRIPTION

Veedol Sintron J 0W-16 is a fuel economy SAE 0W16 motor oil, developed according the most recent technology. It is based on specially selected synthetic base oils and a well balanced choice of advanced additives to give the following benefits:

- Lower fuel consumption
- High and stable viscosity index
- Very fast cold start, even at very low temperatures
- Safe lubrication film at very high temperatures

APPLICATION

This fuel economy SAE 0W16 engine oil is recommended for use in the latest technology petrol engines of passenger cars from Japanese OEMs.

PERFORMANCE SPECIFICATIONS

API SN Plus
API SP/RC
API SN Plus/RC
API SP

Veedol recommends for

Ilsac GF-6 B
Lexus
Toyota

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.846
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	34.8
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	6.9
Viscosity index, ASTM D2270	163
B.N. (HClO ₄ method), ASTM D2896, mg KOH/g	8.5
Flash Point COC, ASTM D92, °C	220
Pour point, ASTM D6892, °C	-45