



Veedol Sintron Longlife IV 0W20

Material no. 03201T029

DESCRIPTION

Veedol Sintron Longlife IV 0W-20 is a full synthetic lubricant mandatory for the newest engines of VW/Audi. It is developed to prolong the life and maintain the efficiency of emission systems. It is also designed to provide outstanding engine cleanliness, wear protection and strong durability to keep the engine running like new. A substantial fuel saving is reached through the use of the ultra low 0W20 viscosity grade. It gives the following benefits:

- Total engine protection: keeps the engine clean
- Fuel economy: superior fuel economy and CO₂ reduction
- Cold start: excellent fluidity at low temperature

APPLICATION

Veedol Sintron Longlife IV 0W-20 is developed for mandatory use in the newest 2.0 TFSI 140 kW and 3.0 TDI CR 160 kW engines of VW and Audi which require the VW specification 508 00 and 509 00.

PERFORMANCE SPECIFICATIONS

ACEA C5

Approvals

VW 508 00/509 00

Veedol recommends for

Porsche C20
VW TL 525 77

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.843
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	40.2
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	8.2
Viscosity index, ASTM D2270	184
B.N. (HClO ₄ method), ASTM D2896, mg KOH/g	8.3
Pour point, ASTM D6892, °C	-51
Sulfated Ash, ASTM D874, Mass %	0.79
Flash Point COC, ASTM D92, °C	235
Colour, VISUAL	GREEN
CCS viscosity at -35°C, ASTM D5293, mPa.s	3500