

Veedol Sintron C5 0W20

Material no. 03201T038

DESCRIPTION

Veedol Sintron C5 0W-20, a full synthetic engine oil, is specifically developed to meet the Opel OV0401547 specification. The ultra low viscosity grade of this lubricant enables the latest engine designs to reach their fuel economy goals. In addition to this, the engine oil forms a powerful layer that absorbs harmful particulates and keeps the engine clean and protected. It gives the following benefits:

- Fuel economy: superior fuel economy and CO₂ reduction
- Cold start: excellent fluidity at low temperature
- After-treatment protection: full after-treatment device protection

APPLICATION

This engine oil offers complete protection to a range of modern passenger car and light truck diesel and gasoline engines, equipped with or without emission after-treatment systems. Furthermore, it can be used in combination with the latest fuel types, such as biofuels and ethanol-based fuels. The API SN Plus specification shows the lubricant's compatibility with highly fuel-efficient GDI engines, in which this oil prevents Low Speed Pre-Ignition (LSPI) from damaging the engine components.

PERFORMANCE SPECIFICATIONS

ACEA C5
API SN/RC/SN Plus
ILSAC GF-5

Approval
MB-Approval 229.71

Veedol recommends for
BMW Longlife-17FE+
GM dexosDTM
Jaguar Land Rover: STJLR.51.5122
Opel OV0401547
Volvo VCC RBS0-2AE

TYPICAL CHARACTERISTICS

Density at 15°C, ASTM D4052, g/ml	0.845
Kinematic viscosity at 40°C, ASTM D445, mm ² /s	40.64
Kinematic viscosity at 100°C, ASTM D445, mm ² /s	8.06
Viscosity index, ASTM D2270	176
B.N. (HClO ₄ method), ASTM D2896, mg KOH/g	7.7
Pour point, ASTM D6892, °C	-57
Sulfated Ash, ASTM D874, Mass %	0.6
Flash Point COC, ASTM D92, °C	210